



NAME	Cavity wall switch-box
Order Nr	202
Type	H3

Description

Solid cavity-wall junction box with 4 screws, 4 conduit entries with up to 20mm and 4 cable passages 3x1,5mm. Maximum wiring space. Maximum variability

- Screws ensure permanent fixing
- Entries can be broken out for cables and conduits
- Combinable and through-wiring by using support connectors
- Fixing of devices by means of pre-mounted device screws

Properties

Color	orange
Degree of protection (IP)	IP30
Free of heavy metals	YES
Halogen-free	YES
Silicone-free	YES
PVC-free	YES
Weather-resistant	IP30

Technical features

Cable entry Ø 20mm	4
Cable insertion	4x20
Installation type	FM

Certificates & standards

CE	YES
Non-Flammability	≤ 850°C
ÖVE	-
RoHS	YES
Design voltage	400 V

Dimensions

Depth	50mm
Lenght	80mm
Width	80mm

Material

Box	Polypropylene (PP)
Lid	-

Environmental conditions

Ambient temperature (24h)	35°C
Ambient temperature (maximum)	40°C
Ambient temperature (minimum)	-25°C
Max. rel. humidity at 25°C (short term)	90%
Max. rel. humidity at 40°C	50%

Accessories

Equipped with	Screws
---------------	--------