#### **OVE AUSTRIAN ELECTROTECHNICAL ASSOCIATION**

Eschenbachgasse 9, 1010 Wien, Austria ZVR: 327279890 | DVR: 1055887

**OVE - Testing & Certification** 

Kahlenberger Str. 2A, 1190 Wien, Austria

Phone: +43 1 370 58 06

www.ove.at



Page 1 of 2

# **ÖVE-CERTIFICATE**

including the entitlement to use the Austrian Safety Mark



Certificate No.: 51923-007-02

Valid from: 2014 08 24

until: 2016 05 20

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company:

BUDVILL Kft.

Körtvelyes u. 12/a 1037 Budapest

Hungary

Product:

Cable duct

Basis for this given right is the conformity of the products with the requirements of the technical standards listed in this certificate as stated in the file(s) Ref.-No(s). TGM-VA EE 34445, TGM-VA EE 34445A.

This certificate establishes the conformity of the tested specimen and of all products manufactured strictly identical to the submitted one.

Österreichischer Verband für Elektrotechnik

Head of Testing & Certification tally signed by K. Wallner

Email=k.wallner@ove.at Dipl.-Ing. W. Martin

Vienna, 2014 06 06

**OVE - Testing & Certification** 

Accredited by the Federal Ministry of Science, Research and Economy as Certification Body for products within the scope as given in the official decree and published under www.en.bmwfw.gv.at/accreditation





Certificate No.: 51923-007-02 Date: 2014 06 06

Page 2 of 2

### Manufacturer:

BUDVILL Kft Orszag út 2-4 1038 Budapest Hungary

## Factory location(s):

BUDVILL Kft Orszag út 2-4 1038 Budapest Hungary

#### Tested and certified according to:

ÖVE/ÖNORM EN 50085-1:2006-05-01 ÖVE/ÖNORM EN 50085-2-1:2007-12-01

This certificate is the basis for the EC Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity with the listed standards as defined by the EC Low-Voltage Directive 2006/95/EC.

Product: Cable duct

Type designation:

Rating:

Trademark:

**BUDVILL** 

15X15

Rated voltage: 400 V Type 1, IP 20

Application temperature: -15 to +90°C

Resistance to impact: 1 J Coulour: white, grey, brown

