OVE AUSTRIAN ELECTROTECHNICAL ASSOCIATION

Eschenbachgasse 9, 1010 Wien, Austria ZVR: 327279890 | DVR: 1055887

OVE - Testing & Certification

Kahlenberger Str. 2A, 1190 Wien, Austria

Phone: +43 1 370 58 06

www.ove.at



Page 1 of 2

ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: 51923-011-01

Valid from: 2015 07 26

until: 2016 05 20

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company:

BUDVILL es Tsa Kft.

Körtvelyes u. 12/a 1037 Budapest

Hungary

Product:

Cable duct

Basis for this given right is the conformity of the products with the requirements of the technical standards listed in this certificate as stated in the file(s) Ref.-No(s). TGM-VA EE 34923.

This certificate establishes the conformity of the tested specimen and of all products manufactured strictly identical to the submitted one.

Österreichischer Verband für Elektrotechnik

Head of Testing & Certification

OVE

Vienna, 2015 05 18

Digitally signed by W. Martin Email=w.martin@ove.at Dipl.-Ing. W. Martin

OVE - Testing & Certification

Accredited by the Federal Ministry of Science, Research and Economy as Certification Body for products within the scope as given in the official decree and published under www.en.bmwfw.gv.at/accreditation





Certificate No.: 51923-011-01

Date: 2015 05 18 Page 2 of 2

Manufacturer:

BUDVILL es Tsa Kft. Orszag út 2-4 1038 Budapest Hungary

Factory location(s):

BUDVILL es Tsa Kft. Fehérítögyár utca 2 1037 Budapest Hungary

Tested and certified according to:

ÖVE/ÖNORM EN 50085-1:2006-05-01 ÖVE/ÖNORM EN 50085-2-1:2012-10-01

This certificate is the basis for the EC Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity with the listed standards as defined by the EC Low-Voltage Directive 2006/95/EC.

Product: Cable duct

Type designation:

Rating:

Trademark:

K5 (15X10)

Rated voltage: 400 V type 1, IP 20

Application temperature: -15 to +90°C

Resistance to impact: 1 J

white

BUDVILL



