



**NAME**  
**Type**

**Cable trunking**  
**K/INSTA**

### Description

Cable trunking systems are designed for installation on walls and ceilings in a range of different finishes. Cable trunking with high form stability and temperature resistance from -5° up to +90°C. Cable trunking systems do have electrical continuity characteristic.

- Easy to install
- Manufactured from high impact white u-PVC, the system is designed to withstand the most rigorous demands of home and office use
- Available with or without self adhesive backing
- Screws intended to be tightened should be done so with a screwdriver at a torque of 2Nm

### Properties

Color	white RAL9010
Degree of protection (IP)	IP20
Free of heavy metals	YES
Halogen-free	YES

Silicone-free	YES
---------------	-----

Weather-resistant	IP20
-------------------	------

### Material

Trunking	PVC
Lid	PVC

### Technical features

400 V	
Mountyng type	surface mounting
Instalation position	can be mounted on a wall or ceiling

### Certificates & standards

CE	YES
Flame retardant	Self-extinguishing
ÖVE	YES
RoHS	YES

Dimensions

Size mm	Lenght mm	Color	Order Nr.
15x15	20000	white	K1
15x15	20000	brown	K1
15x15	20000	grey	K1
30x15	20000	white	K2
30x15	20000	brown	K2
30x15	20000	grey	K2
30x30	20000	white	K3
30x30	20000	brown	K3
30x30	20000	grey	K3
40x40	20000	white	K4
40x40	20000	brown	K4
40x40	20000	grey	K4
12x10	20000	white	INSTA1210
16x10	20000	white	INSTA1610
16x16	20000	white	INSTA1616
22x10	20000	white	INSTA2210
25x17	20000	white	INSTA2517
25x25	20000	white	INSTA2525
30x10	20000	white	INSTA3010
35x15	20000	white	INSTA3515
40x17	20000	white	INSTA4017
40x25	20000	white	INSTA4025
50x25	20000	white	INSTA5025
50x50	20000	white	INSTA5050
60x40	20000	white	INSTA6040
100x50	20000	white	INSTA10050
110x60	20000	white	INSTA11050